

Stainless Steel Wire Mesh (AISI 316)

| mesh type count/inch | count/cm. | mesh opening (µm) | thread Ø (µm) | open area |
|-------------------------|-----------|-------------------|---------------|-----------|
| 12 mesh | 4,7 | 1600 | 500 | 58% |
| 18 mesh | 7,1 | 1100 | 350 | 57% |
| 20 mesh | 7,9 | 930 | 340 | 54% |
| 30 mesh | 11,8 | 590 | 250 | 50% |
| 30 mesh | 11,8 | 650 | 200 | 58% |
| 40 mesh | 15,7 | 415 | 220 | 43% |
| 50 mesh | 19,7 | 308 | 200 | 37% |
| 60 mesh | 23,6 | 270 | 160 | 39% |
| 80 mesh | 31,5 | 200 | 120 | 39% |
| 100 mesh | 39,4 | 144 | 110 | 32% |
| 120 mesh | 47,2 | 122 | 90 | 33% |
| 150 mesh | 59,1 | 105 | 60 | 42% |
| 180 mesh | 70,9 | 81 | 60 | 33% |
| 200 mesh | 78,7 | 77 | 50 | 37% |
| 250 mesh | 98,4 | 62 | 40 | 37% |
| 325 mesh | 128,0 | 44 | 35 | 30% |

Top Zeven b.v.

Wateringweg 34, 2031 EJ Haarlem, Netherlands,

tel +31(0)23 5319051, fax +31(0)23 5319065

filter@topzeven.com , www.topzeven.com